

DATASHEET

BFD SK12



GENERAL

Art.Nr:	L-0096-1	Standards:	EN 354:2010,EN 355:2002
GTIN:	4030281075837	Net weight:	1.24 kg
E-class number:	40-02-01-04	Gross weight:	1.24 kg
Customs tariff number:	56090000		

DATASHEET

BFD SK12

The BFD SK12 is a lanyard with two FS 51 ST karabiners and a strap fall absorber, which reduces the fall energy in case of a fall to a body-compatible level.

FEATURES

Application areas:	Various
Fallindicator:	No
Impact force:	6.00 kN
Colour:	Grey, Black, polyethylene_terephthalate, White
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Rescue loop:	No
Lanyard type:	I-Version

DIMENSIONS

length_lanyard:	1.00 m
Lanyard rope diameter:	12.00 mm

MATERIAL

Material:	Polyamide, Steel
-----------	------------------

DATASHEET

BFD SK12



GENERAL

Art.Nr:	L-0096-1,5	Standards:	EN 354:2010,EN 355:2002
GTIN:	4030281002123	Net weight:	1.28 kg
E-class number:	40-02-01-04	Gross weight:	1.28 kg
Customs tariff number:	56090000		

DATASHEET

BFD SK12

The BFD SK12 is a lanyard with two FS 51 ST karabiners and a strap fall absorber, which reduces the fall energy in case of a fall to a body-compatible level.

FEATURES

Application areas:	Various
Fallindicator:	No
Impact force:	6.00 kN
Colour:	Grey, Black, polyethylene_terephthalate, White
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Rescue loop:	No
Lanyard type:	I-Version

DIMENSIONS

length_lanyard:	1.50 m
Lanyard rope diameter:	12.00 mm

MATERIAL

Material:	Polyamide, Steel
-----------	------------------

DATASHEET

BFD SK12



GENERAL

Art.Nr:	L-0096-2	Standards:	EN 354:2010,EN 355:2002
GTIN:	4030281002130	Net weight:	1.33 kg
E-class number:	40-02-01-04	Gross weight:	1.33 kg
Customs tariff number:	56090000		

DATASHEET

BFD SK12

The BFD SK12 is a lanyard with two FS 51 ST karabiners and a strap fall absorber, which reduces the fall energy in case of a fall to a body-compatible level.

FEATURES

Application areas:	Various
Fallindicator:	No
Impact force:	6.00 kN
Colour:	Grey, Black, polyethylene_terephthalate, White
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Rescue loop:	No
Lanyard type:	I-Version

DIMENSIONS

length_lanyard:	2.00 m
Lanyard rope diameter:	12.00 mm

MATERIAL

Material:	Polyamide, Steel
-----------	------------------