

DATASHEET SKYSAFE PRO+



GENERAL

Art.Nr:	L-0834-1C8	Standards:	EN 354:2010,EN 355: 2002,EN 795:2012/B,
GTIN:	4030281029281		RFU PPE-R/11.074
ernin:	4030201023201	Net weight: 1.15 kg	
E-class number:	40-02-01-04	Net Weight.	1.15 kg
E-class number. 40-02-01-04	Gross weight:	1 15 kg	
Customs tariff number:	56090000		1.15 kg

www.skylotec.com I Datenblatt, 20.10.23



DATASHEET SKYSAFE PRO+

The SKYSAFE PRO+ is a lanyard with a flexible arm and ultra-compact webbing fall arrester that covers a weight range from

50 to 150 kg and reduces the force to less than 6 kN with a maximum fall arrest distance of 1.75m. The sewn-in RESCUE LOOPS allow the casualty

to be lifted with a rescue device in

the event of a fall, relieving the load on the carabiner and facilitating the rescue.

· Compact webbing fall arrester for high freedom of movement

• Universally applicable due to wide weight range from 50 to 150 kg

• Fast and easy rescue thanks to integrated RESCUE LOOPs

FEATURES

Application areas:	Mobile platforms, Working in confined spaces, Elevator construction, Arborists, lithium_ion, Roofers, Facades cleaning, Flat roof construction, Scaffolding, High Rack storage, Off Shore Industry, Rescue, Emergency, Route construction, Shaft, RBA rigging, Steelwork, Telco energy	
Fallindicator:	Yes	
Impact force:	6.00 kN	
Colour:	polyethylene_terephth alate, Black	
Hand wash:	40 °C	
Edge approved:	Yes	
Maximum lifetime:	10 years	
Maximum temperature:	45 °C	
Minimum tensile strength:	22.00 kN	
Minimum temperature:	-35 °C	
Rescue loop:	Yes	
Lanyard type:	I-Version	
DIMENSIONS		
Rope length:	1.80 m	
length_lanyard:	1.80 m	

www.skylotec.com I Datenblatt, 20.10.23



DATASHEET SKYSAFE PRO+

Lanyard rope diameter:	30.00 mm
MATERIAL	
Material:	Polyester, Polyamide, Steel