

# DATASHEET SKYSAFE PRO+



#### **GENERAL**

Art.Nr:	L-0839-1C8
GTIN:	4030281029342
E-class number:	40-02-01-04
Customs tariff number:	56090000

Standards:	EN 354:2010,EN 355: 2002,EN 795:2012/B, RFU PPE-R/11.074
Net weight:	1.66 kg
Gross weight:	1.66 kg



### DATASHEET SKYSAFE PRO+

The SKYSAFE PRO+ is a lanyard with flexible arms and ultra-compact strap fall arrester that covers a weight range from 50 to 150 kg and reduces the force to less than 6 kN with a maximum fall arrest distance of 1.75m. The sewn-in RESCUE LOOPS allow the casualty to be lifted with a rescue device in the event of a fall, relieving the load on the carabiner and facilitating the rescue. Available in four different designs with different carabiner combinations.

- · Compact webbing fall arrester for high freedom of movement.
- · Universally applicable due to wide weight range from 50 to 150 kg.
  • Fast and easy rescue thanks to integrated
- RESCUE LOOPs.

#### **FEATURES**

Application areas:	Mobile platforms, Working in confined spaces, Elevator construction, Arborists, lithium_ion, Roofers, Facades cleaning, Flat roof construction, Scaffolding, High Rack storage, Off Shore Industry, Rescue, Emergency, Route construction, Shaft, RBA rigging, Steelwork, Telco energy
Fallindicator:	Yes
Impact force:	6.00 kN
Colour:	Black, polyethylene_terephth alate
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Rescue loop:	Yes
Lanyard type:	Y-Version
DIMENSIONS	
Rope length:	1.80 m
length_lanyard:	1.80 m



## DATASHEET **SKYSAFE PRO+**

Lanyard rope diameter:

30.00 mm

**MATERIAL** 

Material:

Polyester, Polyamide, Aluminium