

PRODUCT CODE: AJD160-00 - 00

THE LIGHTEST SAFETY HELMET AVAILABLE IN EUROPE

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head



MICROPEAK - SLIP RATCHET - VENTILATED



WEBBING HARNESS: HDPE Strap & Webbing Clips with Polyester Webbing Straps

CHAMLON™ SWEATBAND: Egyptian cotton core with

porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

SLIP RATCHET:

One Touch[™] Slip Ratchet version of the EVOLite® is so simple to fit that it can be adjusted with just one finger





CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

CONFORMITY

EN 397 & FOCT P 50460-92 for Industrial Safety Helmets

EC Certificate Number 00279, issued by BSi Product Certification

Meets optional Lateral Deformation performance

- Wide size range. Slip or wheel ratchet High comfort fit
- Available vented. Available with mid or micro peak
- Company personalisation available by printing



MANUFACTURING FOR SAFETY WWW.JSP.CO.UK

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050



MICROPEAK - SLIP RATCHET - VENTILATED

HEIGHT: 450mm

PRODUCT CODE: AJD160-00_-_00

THE LIGHTEST SAFETY HELMET AVAILABLE IN EUROPE

TECHNICAL SPECIFICATION

HEAD PROTECTION

Yes

Yes

Yes

Yes: EN397 -30°C

Yes

Yes 50 Joules

DIMENSIONS OF OUTER PACKAGING

Quantity: 10 Weight: 3.2kg (Approx.)



HELMET FEATURES

EN397

+50°C

Impact Resistance

Low Temperature

Lateral Deformation

EN STANDARD

PERFORMANCE

TEMPERATURE

RESISTANCE

	State of the second sec	F1391
	USP. EVALUTION UT SAFETY HELMET	Sp
WIDTH: 240mm	www.jsa.co.uk LENGTH: 580mm	

-200

Size:	530 - 640mm		
Weight: 299g (Approx.)			
	ADD YOUR LOGO TO OUR PRODUCTS		

DIMENSIONS OF HELMET

HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



I			FOCT P 50460-92 -30°C
	SHELL MATERIAL	ABS Recyclable UV Stabilised	Yes Yes Yes
	HARNESS MATERIAL	HDPE Textile	Yes Yes
	OPTIONS	Universal Accessories Reflective CR2 option Integrated Eyewear Micro Peak	Yes Yes Yes Yes
	HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
	CHINSTRAP OPTIONS	4 pts 2 pts	Yes Yes
	LOGO OPTIONS	Front Rear Side MOQ Logo	Yes Yes Yes 10

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Individual Name

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



MANUFACTURING FOR SAFETY

UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050

