



PYRAMEX
Perform At Your Peak

Intruder® ANSI CE CSA AUS

Integrated nosepiece

Lightweight, frameless protection

Part No.	Lens and Temples
ES4110S ●●●●	Clear
ES4110ST ●●●●	AF Clear
ES4120S ●●●●	Gray
ES4120ST ●●●●	AF Gray
ES4130S ●●●●	Amber



Intruder Multi-Colors

ANSI CE CSA

Sold in dozen quantity only

Comes with six assorted temple colors: red, blue, green, purple, orange and black

Multi-pack includes two of each temple color with clear lenses

Perfect for schools or work areas where color coding is necessary

Provides a fun assortment of colors to brighten up any work environment

Part No.	Multi-Color Temples
ES4110SMP ●●●●	Clear



There's more to see at
PYRAMEXSAFETY.COM
(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (*) or Australian (AS/NZS 1337) (●) standards.

Intruder®

General Specifications

Weight: 23.1 gm
 PD: 64 mm
 Bridge: 17.27 mm
 Lens base: 10 curve
 Lens size diagonal: 77.08 mm
 Lens size vertical: 43.38 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 156 mm
 Overall width (hinge - hinge): 135.5 mm
 Closest point between temples: 91.53 mm
 Closest point between lens: 16.67 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
ES4110S	2 C - 1.2 P 1 F CE	CE P EN166 F
ES4110ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ES4120S	5 - 2.5 P 1 F CE	CE P EN166 F
ES4120ST	5 - 2.5 P 1 F N CE	CE P EN166 F
ES4130S	2 - 1.2 P 1 F CE	CE P EN166 F
ES4110SMP	2 C - 1.2 P 1 F CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

