

Neshoba™ is one of the lightest weight spectacles on the market, weighing in at 16 grams. To eliminate the threats of an eye injury, an employer should provide workers with products that are comfortable and dependable.







Neshoba™ ANSI • CE • CSA •

Frameless design with thin flexible temples // Ultra lightweight spectacle – 16 gm

Black Temples | 7 Variations

	ES9710S ●●●	Clear
	ES9710ST ●●●	Clear H2X AF
	ES9720S ●●●	Gray
	ES9720ST ●●●	Gray H2X AF
	ES9730S ●●●	Amber
	ES9780S ●●●	I/O Mirror
	ES9780ST ●●●	I/O Mirror AF

Black Temples with Cord | 4 Variations

	ES9710SP ●●●	Clear
	ES9710STP ●●●	Clear H2X AF
	ES9720SP ●●●	Gray
	ES9780SP ●●●	I/O Mirror



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●) or Canadian CSA Z94.3 (●) standards. For specific lens options visit our website or contact your sales representative.

Neshoba™

General Specifications

Weight: 16 gm
 PD: 64 mm
 Bridge: 12.3 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.8 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.6 mm
 Overall length (lens - tip): 151 mm
 Overall width (hinge - hinge): 135 mm
 Closest point between temple tips: 78 mm
 Closest point between lens: 14.5 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
ES9710S	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710SP	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710ST	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710STP	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9720S	5 - 2.5 P 1 F CE	CE P EN166 F
ES9720SP	5 - 2.5 P 1 F CE	CE P EN166 F
ES9720ST	5 - 2.5 P 1 F CE	CE P EN166 F
ES9730S	2 - 1.2 P 1 F CE	CE P EN166 F
ES9780S	5 - 1.7 P 1 F CE	CE P EN166 F
ES9780SP	5 - 1.7 P 1 F CE	CE P EN166 F
ES9780ST	5 - 1.7 P 1 F CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexurope.com