

FS240 FLASH HARNESS

The **FALL SAFE® FS240 - FLASH HARNESS**, is designed for rope access and rescue in order to cover any work situation in fall protection, work positioning and restraint. It's fully adjustable with increased comfort for the most intense work at heights in any hanging direction. Extremely easy to wear, this harness opens totally, allowing it to be dressed as a jacket. The airflow through all the harness layers is assured by the new and improved Croc® 2.0 padding. This innovation also allows for a lighter and more ergonomic final product, which is extremely comfortable for use for several hours. With reflective and extra breathable fabric, the FS240 combines the lightness of its composition with the FALL SAFE® quality assurance.



EAN CODE	SIZE	WEIGHT (KG)
5605423570687	S/M	2,370
5605423571219	L/XL	2,395
5605423571226	XXL	2,420

INTENSITY OF USE
Intensive use ● ● ●

APPLICATIONS
Arborist Confined spaces Rescue Riggers Rope access Telecom towers Tower climbing Wind turbine Wood poles

STANDARDS
EN358:1999 EN361:2002 EN813:2009

FS240 FLASH HARNESS

FEATURES



PHYSICAL PROPERTIES

Metal parts	Aluminium
Webbing	PES HP Water repellent
D-rings	Dorsal D-ring 2 side D-rings for work positioning
Loops	2 front loops for fall arrest 2 ventral loops for sit positioning
Padding	Croc™ 2.0
Adjustment points	7 points
Fall arrest indicators	Yes

OTHER INFORMATION

Device lifespan	10 years
Max. Load	<140 KG
Inspection requirement	Yearly
Traceability	Serial Number/ RFID/ QR Code
Manual Instructions	www.fallsafe-online.com +351 252 480 060