

IGNITE TRION





GENERAL

| Art. no.: | G-1131-S-XS/M |
|-----------|----------------------------|
| EAN: | 4030281230861 |
| Standard: | EN 358:1999 EN 361:2002 |

| E-class number: | 40-02-01-02 |
|-----------------|-------------|
| Customs no.: | 63079098 |



IGNITE TRION

With climbing protection eyelet.

The new high-performance full body harness for industry and trade is uncomplicated and very easy to buckle on. The harness scores with extremely flexible adjustments of belt straps that are passed through the thin but effective hip padding. Due to its asymmetric shape, the padding ensures that the buckle does not exert any pressure in the abdominal area. Ergonomic eyelets are perfectly folded in at the hip without interfering. They are unfolded for use and maintain their position after snapping - if necessary throughout the day. The innovative OKTALOCK click buckles made of stainless steel include new adjustment elements that eliminate undesirable loosening of the belt strap during movement and obviate the need for readjusting during work.

Functionality and ergonomics in abundance:

- asymmetric padding with integrated belt guide
- 4 buckles allow individual adjustments
- retaining eyelets fit the hip ergonomically

FEATURES

| \sim | | |
|--------|--------|----|
| . · O | \cap | r· |
| \sim | ıvu | Ι. |

black / orange / anthracite

| Fall indicator | |
|--------------------------|----------|
| Shoulder or leg padding: | yes |
| Belt strap coiler: | yes |
| Hand-washing: | 40 °C |
| Click buckles: | yes |
| Lanyard Parking-Rings: | yes |
| Max. service life: | 10 Years |
| Max. number of persons: | 1 |
| Rated load: | 140 KG |

Attachment Points:

dorsal attachment point, sternal attachment point, pole strap attachment point, climbing protection evelet

| Сусісі | |
|---------------|----------------------|
| Patent | |
| Back support: | yes |
| Temperature: | from 45 °C to -35 °C |

Area of application:

Construction / Roofer / Carpenter, Facade / Window Cleaning, High Rack, Metal Construction, Power Supplies / -Transmission / Telecommunications, Scaffolding, Wind Energy /

Offshore Industry



DIMENSIONS

| Size: | XS/M |
|-------------|----------|
| Waist size: | 75-125cm |
| Weight: | 2,21 kg |

MATERIAL

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Aluminium

Pole strap attachment point material:

Aluminium

Dorsal attachment point material:

Aluminium

Climbing protection eyelet material:

Aluminium

Material Click buckle: Stainless Steel



IGNITE TRION





GENERAL

| Art. no.: | G-1131-S-XXL/5XL |
|-----------|----------------------------|
| EAN: | 4030281230878 |
| Standard: | EN 358:1999 EN 361:2002 |

| E-class number: | 40-02-01-02 |
|-----------------|-------------|
| Customs no.: | 63079098 |



IGNITE TRION

With climbing protection eyelet.

The new high-performance full body harness for industry and trade is uncomplicated and very easy to buckle on. The harness scores with extremely flexible adjustments of belt straps that are passed through the thin but effective hip padding. Due to its asymmetric shape, the padding ensures that the buckle does not exert any pressure in the abdominal area. Ergonomic eyelets are perfectly folded in at the hip without interfering. They are unfolded for use and maintain their position after snapping - if necessary throughout the day. The innovative OKTALOCK click buckles made of stainless steel include new adjustment elements that eliminate undesirable loosening of the belt strap during movement and obviate the need for readjusting during work.

Functionality and ergonomics in abundance:

- asymmetric padding with integrated belt guide
- 4 buckles allow individual adjustments
- retaining eyelets fit the hip ergonomically

FEATURES

| \sim | | |
|--------|--------|----|
| . · O | \cap | r· |
| \sim | ıvu | Ι. |

black / orange / anthracite

| Fall indicator | |
|--------------------------|----------|
| Shoulder or leg padding: | yes |
| Belt strap coiler: | yes |
| Hand-washing: | 40 °C |
| Click buckles: | yes |
| Lanyard Parking-Rings: | yes |
| Max. service life: | 10 Years |
| Max. number of persons: | 1 |
| Rated load: | 140 KG |

Attachment Points:

dorsal attachment point, sternal attachment point, pole strap attachment point, climbing protection evelet

| eyelet | |
|---------------|----------------------|
| Patent | |
| Back support: | yes |
| Temperature: | from 45 °C to -35 °C |

Area of application:

Construction / Roofer / Carpenter, Facade / Window Cleaning, High Rack, Metal Construction, Power Supplies / -Transmission / Telecommunications, Scaffolding, Wind Energy /

Offshore Industry



DIMENSIONS

| Size: | XXL/5XL |
|-------------|----------|
| Waist size: | 90-140cm |
| Weight: | 2,40 kg |

MATERIAL

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Aluminium

Pole strap attachment point material:

Aluminium

Dorsal attachment point material:

Aluminium

Climbing protection eyelet material:

Aluminium

Material Click buckle: Stainless Steel



IGNITE TRION





GENERAL

| Art. no.: | G-1131-S-M/XXL | E-class numb |
|-----------|----------------------------|--------------|
| EAN: | 4030281230854 | Customs no.: |
| Standard: | EN 358:1999 EN 361:2002 | |

E-class number: 40-02-01-02

Customs no.: 63079098



IGNITE TRION

With climbing protection eyelet.

The new high-performance full body harness for industry and trade is uncomplicated and very easy to buckle on. The harness scores with extremely flexible adjustments of belt straps that are passed through the thin but effective hip padding. Due to its asymmetric shape, the padding ensures that the buckle does not exert any pressure in the abdominal area. Ergonomic eyelets are perfectly folded in at the hip without interfering. They are unfolded for use and maintain their position after snapping - if necessary throughout the day. The innovative OKTALOCK click buckles made of stainless steel include new adjustment elements that eliminate undesirable loosening of the belt strap during movement and obviate the need for readjusting during work.

Functionality and ergonomics in abundance:

- asymmetric padding with integrated belt guide
- 4 buckles allow individual adjustments
- retaining eyelets fit the hip ergonomically

FEATURES

| \sim | | |
|--------|--------|----|
| . · O | \cap | r· |
| \sim | ıvu | Ι. |

black / orange / anthracite

| Fall indicator | |
|--------------------------|----------|
| Shoulder or leg padding: | yes |
| Belt strap coiler: | yes |
| Hand-washing: | 40 °C |
| Click buckles: | yes |
| Lanyard Parking-Rings: | yes |
| Max. service life: | 10 Years |
| Max. number of persons: | 1 |
| Rated load: | 140 KG |

Attachment Points:

dorsal attachment point, sternal attachment point, pole strap attachment point, climbing protection evelet

| eyelet | |
|---------------|----------------------|
| Patent | |
| Back support: | yes |
| Temperature: | from 45 °C to -35 °C |

Area of application:

Construction / Roofer / Carpenter, Facade / Window Cleaning, High Rack, Metal Construction, Power Supplies / -Transmission / Telecommunications, Scaffolding, Wind Energy /

Offshore Industry



DIMENSIONS

| Size: | M/XXL |
|-------------|----------|
| Waist size: | 80-130cm |
| Weight: | 2,30 kg |

MATERIAL

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Aluminium

Pole strap attachment point material:

Aluminium

Dorsal attachment point material:

Aluminium

Climbing protection eyelet material:

Aluminium

Material Click buckle: Stainless Steel