

# **IGNITE PROTON WIND STEEL**





### **GENERAL**

Art. no.:	G-1132-WS-ST-XS/M	E-class number:	40-02-01-02
EAN:	4030281237761	Customs no.:	63079098
Standard:	EN 358:2018 EN 361:2002		



# IGNITE PROTON WIND STEEL

This completely equipped body harness for fall arrestingThis professional and completely equipped body harness for fall arresting, work positioning and climbing protection with a synthetic sliding plate was developed specially for the wind energy industry. It can be used in many other areas as well when top performance in safety and functionality are required. IGNITE PROTON scores with thermoshaped hip padding that evenly distributes weight and is protected from wear and tear on the outside with a synthetic plate. The welldesigned construction allows the fall-arrest attachment point to be perfectly positioned for the user. It also offers practical belt strap coilers to eliminate bulky excess length. Shoulder and leg padding can be laundered or replaced. Pre-formed gear loops and tool eyelets for different kinds of use make the harness a complete system.

- Can be used with all carabiner openings of 10.5 mm and up
- Thermo-shaped waist padding
- Replaceable shoulder and leg padding

Internat. standard:

ANSI Z359.11:2014, MEETS CSA Z259.10:2012

#### **FEATURES**

$C \cap$	lour:	
CO	oui.	

black / orange / anthracite	9
Fall indicator	
Shoulder or leg padding:	yes
Belt strap coiler:	yes
Hand-washing:	40 °C
Click buckles:	yes
Synthetic Slide Plate:	yes
Lanyard Parking-Rings:	yes
Gear loop:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	140 KG
Attachment Points:	
dorsal attachment point, s pole strap attachment poi eyelet	

Patent
Back support: yes
Temperature: from 45 °C to -35 °C
Area of application:
Wind Energy / Offshore Industry
Tool loop: yes



#### **DIMENSIONS**

Size:	XS/M	
Waist size:	74-121cm	_
Weight:	3,10 kg	_

#### **MATERIAL**

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Steel

Pole strap attachment point material:

Aluminium

Dorsal attachment point material:

Aluminium

Climbing protection eyelet material:

Steel

Material Click buckle: Stainless Steel



# **IGNITE PROTON WIND STEEL**





### **GENERAL**

Art. no.:	G-1132-WS-ST-M/XXL	E-class nun
EAN:	4030281237747	Customs no
Standard:	EN 358:2018 EN 361:2002	

E-class number:	40-02-01-02
Customs no.:	63079098



#### **GENERAL IGNITE PROTON WIND**

This completely equipped body harness for fall arrestingThis professional and completely equipped body harness for fall arresting, work positioning and climbing protection with a synthetic sliding plate was developed specially for the wind energy industry. It can be used in many other areas as well when top performance in safety and functionality are required. IGNITE PROTON scores with thermoshaped hip padding that evenly distributes weight and is protected from wear and tear on the outside with a synthetic plate. The welldesigned construction allows the fall-arrest attachment point to be perfectly positioned for the user. It also offers practical belt strap coilers to eliminate bulky excess length. Shoulder and leg padding can be laundered or replaced. Pre-formed gear loops and tool eyelets for different kinds of use make the harness a complete system.

- Can be used with all carabiner openings of 10.5 mm and up
- Thermo-shaped waist padding
- Replaceable shoulder and leg padding

Internat. standard:

ANSI Z359.11:2014, MEETS CSA Z259.10:2012

#### **FEATURES**

Colour:	Colour	olour:			
black / orange / anthracite	black /	ack / or	ange /	anthr	acite

biabit, biaingo, antinabit	
Fall indicator	
Shoulder or leg padding:	yes
Belt strap coiler:	yes
Hand-washing:	40 °C
Click buckles:	yes
Synthetic Slide Plate:	yes
Lanyard Parking-Rings:	yes
Gear loop:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	140 KG
Attachment Points:	

dorsal attachment point, sternal attachment point, pole strap attachment point, climbing protection eyelet

Patent	
Back support:	yes
Temperature:	from 45 °C to -35 °C
Area of application:	
Wind Energy / Offshore	e Industry
Tool loop:	yes



#### **DIMENSIONS**

Size:	M/XXL
Waist size:	91-124cm
Weight:	3,10 kg

#### **MATERIAL**

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Steel

Pole strap attachment point material:

Aluminium

Dorsal attachment point material:

Aluminium

Climbing protection eyelet material:

Steel

Material Click buckle: Stainless Steel



# **IGNITE PROTON WIND STEEL**





### **GENERAL**

Art. no.:	G-1132-WS-ST- XXL/5XL	E-class number:	40-02-01-02
EAN:	4030281237754	Customs no.:	63079098
Standard:	EN 358:2018 EN 361:2002		



#### **GENERAL IGNITE PROTON WIND**

This completely equipped body harness for fall arrestingThis professional and completely equipped body harness for fall arresting, work positioning and climbing protection with a synthetic sliding plate was developed specially for the wind energy industry. It can be used in many other areas as well when top performance in safety and functionality are required. IGNITE PROTON scores with thermoshaped hip padding that evenly distributes weight and is protected from wear and tear on the outside with a synthetic plate. The welldesigned construction allows the fall-arrest attachment point to be perfectly positioned for the user. It also offers practical belt strap coilers to eliminate bulky excess length. Shoulder and leg padding can be laundered or replaced. Pre-formed gear loops and tool eyelets for different kinds of use make the harness a complete system.

- Can be used with all carabiner openings of 10.5 mm and up
- Thermo-shaped waist padding
- Replaceable shoulder and leg padding

Internat. standard:

ANSI Z359.11:2014, MEETS CSA Z259.10:2012

#### **FEATURES**

Colour:	Colour	olour:			
black / orange / anthracite	black /	ack / or	ange /	anthr	acite

black orange , and had	
Fall indicator	
Shoulder or leg padding:	yes
Belt strap coiler:	yes
Hand-washing:	40 °C
Click buckles:	yes
Synthetic Slide Plate:	yes
Lanyard Parking-Rings:	yes
Gear loop:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	140 KG
Attachment Points:	

dorsal attachment point, sternal attachment point, pole strap attachment point, climbing protection eyelet

Patent		
Back support:	yes	
Temperature:	from 45 °C to -35 °C	
Area of application:		
Wind Energy / Offshore Industry		
Tool loop:	yes	



#### **DIMENSIONS**

Size:	XXL/5XL
Waist size:	102-138cm
Weight:	3,17 kg

#### **MATERIAL**

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Steel

Pole strap attachment point material:

Aluminium

Dorsal attachment point material:

Aluminium

Climbing protection eyelet material:

Steel

Material Click buckle: Stainless Steel