


Data sheet

**SKYSAFE PRO FLEX Y**



**GENERAL**

Art. no.:	L-0559-1,8
EAN:	4030281180654
Standard:	EN 354:2010 EN 355:2002

E-class number:	40-02-01-04
Customs no.:	56090000

## Data sheet

# SKYSAFE PRO FLEX Y

### ONE4ALL - The SKYSAFE PRO

Revolutionary, new, patented energy absorber with the large weight range from 50 - 140kg (110 - 310 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet).

The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product.

**UNIQUE:** The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue!

Available in four versions with different carabiner combinations:  
I-web, Y-web, I-web tie-back, Y-web tie-back.

### FEATURES

Fall indicator

Breaking load, major axis:

22 kN

Hand-washing: 40 °C

Suitable for edges: yes

Max. service life: 4-6

Max. number of persons: 1

Patent

Rescue Loop: yes

Temperature:

from -35 °C to +45 °C

Suspension element: Webbing

Area of application:

Fire brigade / Rescue / Special Forces, Power Supplies / -Transmission / Telecommunications

## DIMENSIONS

Size: 1,8m

Weight: 1.827

## HARDWARE

Carabiner on anchoring point side:

FS 90 ALU

Carabiner on belt side: STAK TRI

## MATERIAL

Material: Aluminium, Polyester

Webbing material: PES